



SUNVIS





HYDRAULIC FLUIDS

Hydraulic lubricants manufactured from highly refined/pure base oils and fortified with specially selected additives to ensure an optimal performance in the hydraulic system.

MINERAL

SUNVIS 800 WR HV



Universally applicable hydraulic fluid. Suitable for all types of hydraulic systems.

ISO 10 / 15 / 22 / 32 / 16 / 68 / 100 / 150

DIN 51524 Part 2 (HLP)

ISO 11158 (HM)

AFNOR NF E 48-603 HM

CINCINNATI MACHINE P-68 / P-69 / P-70

DENISON HF-0 / HF-1 / HF-2

SUNVIS HV



High-performance universal hydraulic oil with a high viscosity index. Very stable, withstanding wide temperature variations and heavy loads.

ISO 15 / 22 / 32 / 16 / 68

DIN 51524 Part 2 & 3 (HLP/HVLP)

DIN 51502 HVLDP

ISO 6743/4 HV

SUNVIS 800 ZF



Zinc-free hydraulic oil formulated from highly refined mineral bases of paraffinic nature and carefully selected additives, ash-free, providing this fluid with an excellent natural viscosity index, good anti-wear properties and high resistance to oxidation.

ISO 32 / 46 / 68

DIN 51524 Part 2 (HLP)

ISO 11158 (HM)

ISO 6743/4 HM

AFNOR NF E 48-603 HM

SUNVIS 700 HV



High-quality, detergent and dispersant hydraulic oil, applicable in case of wide temperature variations. Offers optimum protection against rust, wear and corrosion. Keeps the hydraulic system very clean.

ISO 32 / 46 / 68

DIN 51524 Part 2 & 3 (HLP/HVLP)

DIN 51502 HVLDP

ISO 6743/4 HV

AFNOR NF E 48-603 HVLP

CINCINNATI MACHINE P-68 / P-69 / P-70

DENISON HF-0 / HF-1 / HF-2

SUNVIS 900



Lubricating oil formulated from highly refined paraffinic base oils and enforced with specially selected additives to prevent oxidation, rust and foam.

ISO 32 / 46 / 68

DIN 51524 Part 1 (HL)

ISO 6743-4 (HL)

DIN 51517 (CL)

ISO 6743-2 (FC)



SUNVIS POCLAIN 5051-A



High-quality and performance hydraulic oil specifically designed for equipment operating under very severe operating conditions, high demands and difficult environmental conditions and with significant temperature fluctuations.

ISO 46

DIN 51524 Part 2 & 3 (HLP/HVLP)

DIN 51502 HVLP

POCLAIN P10032-79V

SYNTHETIC

SUNVIS 1000 AW HVI



Truly multipurpose hydraulic oils, specially developed for applications subjected to a wide range of temperatures or where minimum viscosity change, with fluctuating temperatures, is required. They are formulated with severely hydro-treated base oils, a highly shear stable polymer and an advanced additive system to meet the stringent requirements of modern hydraulic systems.

ISO 32 / 46 / 68

DIN 51524 Part 3 (HVLP)

ISO 11158 (HV)

AFNOR NF E 48-603 HV



High-performance and long-lasting hydraulic fluid.



Truly multipurpose hydraulic fluid. Due to its technical properties this fluid is suitable for replacing many of the existing hydraulic fluids.



Rapidly biodegradable product. Environmentally friendly.



High natural viscosity index (HVI). Excellent stability and minimum changes of viscosity when working under high pressures and temperatures.



Zinc free. Clean and pure fluid.



Very high flash point.



Extremely low pour point, lower than -40°C . Ideal for those hydraulic systems working under very low temperatures.





ECOVIS S



Biodegradable hydraulic oil with a high viscosity index. Fully synthetic lubricant, ecological and biodegradable, formulated from esters bases and a specially selected additive package. Suitable for systems operating at high pressures.

ISO 32 / 46 / 68

DIN 51524 Part 2&3 (HLP/HVLP)

ISO 11158 (HR/HV)

ISO 15380 – HEED

VDMA 24568 – HEES

ISO 12922 HFDU

RACING RS 1



High-performance synthetic fluid to be used as a mean of power transmission in extreme situations. Extremely high viscosity index, superior to 350. Very stable hydraulic fluid
ISO 15

DIN 51524 Part 2 & 3 (HLP/HVLP)

DIN 51502 HVLPD

ISO 6743/4 HV

SUNVIS FHI 46E



Fire-resistance hydraulic fluid indicated for power transmission system working under severe temperature changes. This product is formulated from synthetic esters and specially selected additives to be able to operate at a wide range of temperatures with an excellent stability.

ISO 46

ISO 6743/4 - HFDU

SUNVIS FHI 365G



High quality, aqueous-based, hydraulic lubricant. Formulated from a water-glycol mixture. Suitable for those hydraulic system where a fire-resistant hydraulic fluid is required.

ISO 46

ISO 6743/4 - HFC



Multifunctional lubricant. Suitable for various applications



Industrial gears



High temperatures



Very low temperatures



Heavy loads



Biodegradables



Fire-resistance fluid



Zinc free (ash less) formulation



Air compressors and vacuum pumps

SYNTHETIC AND FOOD GRADE

SUNFOOD MPF



Multipurpose and food grade oils. Formulated from synthetic base oils and specially selected additives. Non-toxic lubricants indicated for its use in the food industry, in those applications where accidental contact with food is possible.

ISO 32 / 46 / 68 / 100 / 150 / 220 / 320
460 / 680 / 1000

DIN 51524 Part 2 - HLP
DIN 51517 Part 3 - CLP
DIN 51506 - VDL
NSF H1 / Kosher / Halal

SUNFOOD MPF FS



Multipurpose and food grade oils. Formulated from fully synthetic base oils - Polyalphaolefin (PAO) - and specially selected additives. Non-toxic lubricants, indicated for use in the food industry, in those applications where accidental contact with food is possible.

ISO 15 / 32 / 46 / 68 / 100

DIN 51524 Part 3 - HVLP
DIN 51506 - VDL
NSF H1 / Kosher / Halal



The information contained in this flyer reflects the current state of our knowledge and research. Depending on the use, the technical behavior of the lubricants may vary. Therefore, in case of doubt we always recommend you to contact us. Since our products are constantly developing, we reserve the right to modify any information contained in this catalogue in any moment. The reproduction, in whole or in part, of this catalogue without the authorization of the company Sun Oil España S.A. is forbidden. Date of last edition: 01/06/2025 (All previous versions are cancelled as of this update).